

OASIS®



Capacity: 10/15kg

Features

- Softmount with springs and shock absorbers.
- Washer features the uniquely designed 3D stereoscopic honeycomb-shaped inner drum with perforated lifters.
- Stainless steel washer drum and tub.
- Stainless steel dryer cylinder.
- 10kg washer utilize direct drive motor without belt and pulley.
- Dryer features axial-radial airflow.
- Front lint filter drawer makes clean lint easier.
- Standard 4 chemical compartments and 5 hoses for dosing pump.
- Mechanical and electronic double door lock and emergency stop.
- Advanced inverter drive system.
- Easy to access service parts from front and back panels.

Control

- Full-color touchscreen control offers 50 programs for OPL and 6 for vend.
- Freely programmable and available in multiple languages.
- USB connection and networking capability.
- Vend audit data, service audit data and remaining time indicator.
- Payment options available in coin, card, mobile pay,


Options

- Electric heating for washer.
- Electric or gas heating for dryer.
- Contact us for other requests.


——High-end commercial and industrial laundry equipment manufacturer.

Specifications		XH10F		XH15F	
Contol		Touch		Touch	
Activation		OPL/Vend		OPL/Vend	
		Washing	Drying	Washing	Drying
Capacity	kg	10		15	
Cylinder Diameter	mm	532	658	600	720
Cylinder Depth	mm	405	500	478	635
Volume	liter	90	170	135	258
Door Center to Floor	mm	543	1566	643	1630
Cold Water Inlet	inch	1/2	-	1/2	-
Hot Water Inlet	inch	1/2	-	1/2	-
Chemical Flushing	inch	-	-	3/4	-
Drain Diameter (pump/valve)	mm	22/51	-	51	-
Extraction Speed Max	RPM	1000	-	940	-
G-force		300	-	300	-
Reversing Cylinder		Yes	Yes	Yes	Yes
Drive motor	kW	0.8	0.25	0.75	0.25
Fan motor	kW	-	0.25	-	0.25
Single phase heating power	kW	3	7.5	6	10.5
Three-phase heating power	kW	9	7.5	9	10.5
Gas Inlet	inch	-	1/2	-	1/2
Exhaust	mm	-	110	-	160
Power Supply		220V/50Hz/60Hz/1ph 380V/50Hz/60Hz/3ph		220V/50Hz/60Hz/1ph 380V/50Hz/60Hz/3ph	
		Contact us for other voltages			
Overall Width	mm	710		800	
Overall Depth	mm	859		1018	
Overall Height	mm	1937		2111	
Net Weight	kg	260		360	
Packing Width	mm	810		900	
Packing Depth	mm	959		1118	
Packing Height	mm	2079		2211	


Oasis preserves the right to change the machines and the specification at any time without prior notice.




Front side



Left side



Rear side



Upper side

- | | | |
|---------------|----------------|--------------------------|
| 1.Lint filter | 6.Washing door | 11.Hot water |
| 2.Soap | 7.Cable | 12.External liquidsupply |
| 3.Dry door | 8.Switch | 13.Gas |
| 4.Coin | 9.Drainage | 14.Exhaust |
| 5.Controller | 10.Cold water | |



Jinan Oasis Dry Cleaning and Laundry Equipment Co.,Ltd.

☎ Tel: +86-531-85701288 85711288

✉ E-mail: inquiry@oasisle.com

Ⓜ Http://www.oasislaundrygroup.com

📍 Add: No.39, Lan Xiang Middle Road, Jinan City, China